



- 12-7081 ENCLOSURE SYSTEMS FRONT MOUNT FAN TRAY 2 fans, on/off switched, grey
- 12-7082 ENCLOSURE SYSTEMS FRONT MOUNT FAN TRAY 2 fans, on/off switched, black
- 12-7083 ENCLOSURE SYSTEMS FRONT MOUNT FAN TRAY 4 fans, on/off switched, grey
- 12-7084 ENCLOSURE SYSTEMS FRONT MOUNT FAN TRAY 4 fans, on/off switched, black

- 12-7089 ENCLOSURE SYSTEMS FRONT MOUNT FAN TRAY 2 fans, on/off switched, with thermostat, grey
- 12-7090 ENCLOSURE SYSTEMS FRONT MOUNT FAN TRAY 2 fans, on/off switched, with thermostat, black
- 12-7091 ENCLOSURE SYSTEMS FRONT MOUNT FAN TRAY 4 fans, on/off switched, with thermostat, grey
- 12-7092 ENCLOSURE SYSTEMS FRONT MOUNT FAN TRAY 4 fans, on/off switched, with thermostat, black

ENCLOSURE SYSTEMS RACK FANS

Universal mounting 1U units available with 2 or 4 fans, with or without an analogue thermostat to ensure efficient cooling of all electronic equipment. Front panels are finished in either RAL9005 black or RAL 7035 grey, and are fitted with an illuminated mains rocker switch. Power supply 220/240VAC via captive mains cable fitted with a UK 3-pin plug. Thermostat models connected to the analogue thermostat via a 1.5M cable. Thermostat operating range 0 – 35 degrees.

Specifications:

Air flow capacity (per fan)	2.3 to 3m ³ per minute
Fan speed	2550-2750 rpm
Fan noise	42 - 47dB
Fan lifespan	50000 Hours
Power source	220/240V AC, 50/60Hz, 13.8/11.8W
Airflow	Upwards

Dimensions:

2 fan models	1U x 19" x 150mm (d)
4 fan models	1U x 19" x 300mm (d)